

Leica FlexLine TS02plus

Best-In-Class Precision



- when it has to be **right**

Leica
Geosystems

Leica FlexLine plus

Proven Specifications, Reliable Instruments

Angle Measurement (Hz, V)		
Accuracy ¹⁾	3" (1 mgon) / 5" (1.5 mgon) 7" (2 mgon)	✓
Method	Absolute, continuous, diametrical: at all models	✓
Display resolution	0.1" / 0.1 mgon / 0.01 mil	✓
Compensation	Quadruple Axis compensation: at all models	✓
Compensator Setting Accuracy	1" / 1.5" / 2"	✓
Distance Measurement with Reflector		
Range ²⁾ Round prism (Leica GPR1)	3.500 m	✓
Range ²⁾ Reflective tape (60 mm x 60 mm)	250m > 500 m ⁸⁾	✓
Accuracy ³⁾	Precise+: 1.5 mm + 2.0 ppm Precise Fast: 2.0 mm + 2.0 ppm Tracking: 3.0 mm + 2.0 ppm	✓
Typical Measurement time ⁴⁾	2.0 s	✓
Distance Measurement without Reflector ⁷⁾		
Range ⁵⁾ PinPoint R500	500 m	○
Accuracy ³⁾	2 mm + 2 ppm	✓
Laser dot size	At 30 m: approx. 7 x 10 mm At 50 m: approx. 8 x 20 mm	✓
Data storage / Communication		
Internal memory	Max.: 24'000 fixpoints, Max.: 13'500 measurements	✓
Interfaces	Serial (Baudrate up to 115'200)	✓
Data formats	GSI / DXF / LandXML / CSV / user definable ASCII formats	✓
Telescope		
Magnification / Resolving power	30 x / 3"	✓
Field of View	1° 30' (1.66 gon) 2.7 m at 100 m	✓
Focusing range	1.7 m to infinity	✓
Reticle	Illuminated, 10 brightness levels	✓

Keyboard and Display		
Keyboard and Display	Simple Alpha-numerical keyboard with high resolution Black & White display, Graphics, 160 x 288 pixels, display illuminated, 5 brightness levels	✓
Position	Face I, Face II	✓○
Operating System		
Windows CE	5.0 Core	✓
Laserplummet		
Type	Laser point, 5 brightness levels	✓
Centering accuracy	1.5 mm at 1.5 m	✓
Battery		
Type	Lithium-Ion	✓
Operating time ⁶⁾	approx. 30 hours	✓
Weight		
TS including GEB211 and tribrach	5.1 kg	✓
Environmental		
Temperature range (operation)	-20° C to +50° C (-4° F to +122° F) Arctic Version -35° C to 50° C (-31° F to +122° F)	✓ ○
Dust / Water (IEC 60529) Humidity	IP55, 95%, non condensing	✓
Leica FlexField plus Onboard Software		
Included Application Programs: Topography; Stake Out; Station Setup including: Resection, Local Resection, Helmert Resection, Orientation (Angles & Coordinates), Height Transfer; Area (Plan & Surface); DTM Volume calculation; Tie Distance (MLM); Remote Height; Hidden Point; Backsight Check; Offset; Reference Line;		✓
Extra Application Programs: Reference Arc; Reference Plane; COGO; Road 2D		○
Theft protection		
mySecurity, PIN/PUK Code		✓✓

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2013. 806061en - 1.13 - galledia

Model Comparison: Configurations & Options of Manual Total Stations

	TS02plus	TS06plus	TS09plus	Viva TS11
1" angular accuracy	-	○	○	○
Enhanced measurement accuracy to prism	1.5 mm + 2 ppm	1.5 mm + 2 ppm	1.5 mm + 2 ppm	1.0 mm + 1.5 ppm
Reflectorless measurement range	500 m option	500 m included/1000 m option	500 m included/1000 m option	500 m included/1000 m option
Display with graphics and display illumination	Black & White high resolution	Black & White high resolution	Q-VGA Color & Touch	Full-VGA Color & Touch
Full alpha-numerical keyboard with function keys	-	✓	✓	✓
Second Keyboard	○	○	○	○
Keyboard illumination	-	-	✓	✓
Electronic Guide Light	-	○	✓	✓
USB Type A and mini B	-	✓	✓	✓
Bluetooth® Wireless	-	✓	✓	✓
SD Card	-	-	-	✓
Imaging capability	-	-	-	○
Smart Station GNSS capability	-	-	-	○
Onboard software (package content)	FlexField plus (standard)	FlexField plus (advanced)	FlexField plus (full)	SmartWorx Viva (pro)

Legend:

- 1) Standard deviation ISO-17123-3
- 2) Overcast, no haze, visibility about 40 km; no heat shimmer.
- 3) Standard deviation ISO-17123-4
- 4) Prism Precise Fast mode

- 5) Under optimal conditions on Kodak Grey Card (90% reflective). Maximum range varies with atmospheric conditions, target reflectivity and surface structure.
- 6) Single Measurement every 30 second at 25° C. Battery time may be shorter if battery is not new. Internal battery GEB222.

- 7) Reflectorless measurement time may vary according to measuring objects, observation situations and environmental conditions.
- 8) with R500 option using Non-prism mode

- ✓ Included
- Option
- Not available



Total Quality Management - our commitment to total customer satisfaction.

Distance meter: (PinPoint R500): Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1

Distance meter: (Prism Mode) Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1

Laser plummet: Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1

Cover picture: Los Angeles skyline

Leica Geosystems AG
Heerbrugg, Switzerland
www.leica-geosystems.com

Scan the code to play the videos!



- when it has to be right

