

Specifications

Trimble SPS855 GNSS Modular Receiver



Receiver Name

SPS855 GNSS Modular Receiver

Configuration Option

Base and Rover interchangeability
Rover position update rate
Rover maximum range from base radio
Rover operation within a VRS™ network
Heading and Moving Base operation
Factory options

Yes, upgradeable to Rover, Base or Rover / Base
1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz
Unrestricted, typical range 2–5 km (1.2–3 miles) without radio repeater
Yes
Yes - option⁷
See Receiver Upgrades below

General

Keyboard and display

Vacuum Fluorescent display 16 characters by 2 rows. Invertable
On/Off key for one-button startup
Escape and Enter keys for menu navigation
4 arrow keys (up, down, left, right) for option scrolls and data entry
24 cm × 12 cm × 5 cm (9.4 in × 4.7 in × 1.9 in) including connectors
1.65 kg (3.64 lb) receiver with internal battery and radio
1.55 kg (3.42 lb) receiver with internal battery and no radio

Dimensions (L × W × D)

Weight

Antenna Options

GA510
GA530
GA810

L1/Beacon, DSM 232
Zephyr™ Model 2
Zephyr Geodetic™ Model 2
Zephyr Model 2 Rugged
Zephyr, Zephyr Geodetic, Z-Plus, Micro-Centered™

L1/L2/L2C GPS, SBAS, and OmniSTAR
L1/L2/L2C GPS, SBAS, and OmniSTAR
L1/L2/L2C GPS, Glonass, Galileo, Compass, OmniSTAR, SBAS (optimized for
OmniSTAR)
Not Supported
L1/L2/L2C/L5 GPS, Glonass, Galileo, Compass, OmniSTAR, SBAS
L1/L2/L2C/L5 GPS, Glonass, Galileo, Compass, OmniSTAR, SBAS
L1/L2/L2C/L5 GPS, Glonass, Galileo, Compass, OmniSTAR, SBAS
Refer to Antenna specification

Temperature

Operating¹
Storage
Humidity
Waterproof

-40 °C to +65 °C (-40 °F to +149 °F)
-40 °C to +80 °C (-40 °F to +176 °F)
MIL-STD 810F, Method 507.4
IP67 for submersion to depth of 1 m (3.3 ft), dustproof

Shock and Vibration

Pole drop
Shock – Non-operating
Shock – Operating
Vibration

Designed to survive a 1 m (3.3 ft) pole drop onto a hard surface
To 75 g, 6 ms
To 40 g, 10 ms, saw-tooth
Tested to Trimble ATV profile (4.5 g RMS): 10 Hz to 300 Hz: 0.04 g/Hz²
300 Hz to 1,000 Hz; –6 dB/octave

Specifications

Trimble SPS855 GNSS Modular Receiver

Measurements

Advanced Trimble Maxwell™ 6 Custom GPS Chips
High-precision multiple correlator for GNSS pseudorange measurements
Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low-time domain correlation, and high-dynamic response
Very low noise carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
Trimble EVEREST™ multipath signal rejection
L-Band: OmniSTAR VBS, HP, XP, G2 by subscription
GPS L1 C/A, L2C, L2E (Trimble method for tracking unencrypted L2P) upgradable to L5. 440 channels
Upgradeable to GLONASS L1/L2C/A, L1/L2P Full Cycle Carrier
Upgradeable to Galileo: L1 CBOC, E5A, E5B & E5AltBOC⁸
Upgradeable to Compass: B1, B2, B3
4-channel SBAS L1 C/A, L5 (WAAS/EGNOS/MSAS)
QZSS: L1 C/A, L1C, L1 SAIF, L2C, L5

SBAS (WAAS/EGNOS/MSAS) Positioning³

Accuracy Better than 5 m 3DRMS (16 ft)

Code Differential GPS Positioning²

Horizontal accuracy 0.25 m + 1 ppm RMS (0.8 ft + 1 ppm RMS)

Vertical accuracy 0.50 m + 1 ppm RMS (1.6 ft + 1 ppm RMS)

OmniSTAR Positioning

VBS service accuracy Horizontal <1 m (3.3 ft)

XP service accuracy Horizontal 0.2 m (0.66 ft), Vertical 0.3 m (1.0 ft)

HP service accuracy Horizontal 0.1 m (0.33 ft), Vertical 0.15 m (0.5 ft)

Location RTK Positioning

Horizontal accuracy Location RTK (10/10) or (10/2) 10 cm + 1 ppm RMS (0.32 ft + 1 ppm)

Vertical accuracy Location RTK (10/10) 10 cm + 1 ppm RMS (0.32 ft + 1 ppm)

Location RTK (10/2) 2 cm + 1 ppm RMS (0.065 ft + 1 ppm)

Real-Time Kinematic (RTK up to 30 km)

Positioning²

Horizontal accuracy 8 mm + 1 ppm RMS (0.026 ft + 1 ppm RMS)

Vertical accuracy 15 mm + 1 ppm RMS (0.05 ft + 1 ppm RMS)

Trimble VRS⁹

Horizontal accuracy 8 mm + 0.5 ppm RMS (0.026 ft + 0.5 ppm)

Vertical accuracy 15 mm + 0.5 ppm RMS (0.05 ft + 0.5 ppm)

Precise Heading

Heading accuracy Combined with SPS555H⁷

2 m antenna separation 0.09° RMS

10 m antenna separation 0.05° RMS

Initialization Time

Regular RTK operation with base station Single/Multi-base

typically less than 8 seconds

Initialization reliability⁴ >99.9%

Power

Internal Integrated internal battery 7.2 V, 7800 mA-hr, Lithium-ion

Internal battery operates as a UPS during an ext power source failure

Internal battery will charge from external power source as long as source can

support the power drain

Integrated charging circuitry

Specifications

Trimble SPS855 GNSS Modular Receiver

Power

External

Power input on 7-pin 0-shell Lemo connector is optimized for lead acid batteries with a cut-off threshold of 11.5 V

Power input on the 26-pin D-sub connector is optimized for Trimble lithium-ion battery input with a cut-off threshold of 10.5 V

Power source supply (Internal/External) is hot-swap capable in the event of power source removal or cut off

DC external power input with over-voltage protection

Receiver automatically turns on when connected to external power
N/A

Power over Ethernet (PoE)

Power consumption

6.0 W in rover mode with internal receive radio
8.0 W in base mode with internal transmit radio

Operation Time on Internal Battery

Rover

13 hours; varies with temperature

Base station

450 MHz systems

Approximately 11 hours; varies with temperature⁵

900 MHz systems

Approximately 9 hours; varies with temperature

Regulatory Approvals

FCC: Part 15 Subpart B (Class B Device) and Subpart C, Part 90
Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

Canadian RSS-310, RSS-210, and RSS-119.

Cet appareil est conforme à la norme CNR-310, CNR-210, et CNR-119 du Canada.

R&TTE Directive: EN 301 489-1/-5/-17, EN 300 440, EN 300 328, EN 300 113, EN 60950, EN 50371

ACMA: AS/NZS 4295 approval

CE mark compliance

C-tick mark compliance

UN ST/SG/AC.10.11/Rev. 3, Amend. 1 (Lithium-ion Battery)

UN ST/SG/AC. 10/27/Add. 2 (Lithium-ion Battery)

RoHS compliant

WEEE compliant

Communications

Lemo (Serial)

7-pin 0S Lemo, Serial 1, 3-wire RS-232

Modem 1 (Serial)

26-pin D-sub, Serial 2, Full 9-wire RS232, using adaptor cable

Modem 2 (Serial)

26-pin D-sub, Serial 3, 3 wire RS-232, using adaptor cable

1PPS (1 Pulse-per-second)

Available on Marine versions

Ethernet

Through a multi-port adaptor

WiFi

N/A

Bluetooth wireless technology

Fully-integrated, fully-sealed 2.4 GHz Bluetooth module⁶

Integrated radios (optional)

Fully-integrated, fully-sealed internal 410-470 MHz Tx/Rx; Internal 900 MHz Tx/Rx

Channel spacing (450 MHz)

12.5 kHz or 25 kHz spacing available

Sensitivity (450 MHz)

-114 dBm (12 dB SINAD)

450 MHz output power

0.5 W, 2.0 W (2.0 W available only in certain countries)

900 MHz output power

1.0 W

Frequency approvals (902-928 MHz)

USA/Canada

External GSM/GPRS, cell phone support

Supported for direct-dial and Internet-based correction streams – directly using the external SNM940 or using the SCS900 software

Cell phone or GSM/GPRS modem inside controller or external SNM940

Specifications

Trimble SPS855 GNSS Modular Receiver

Internal MSK Beacon receiver

N/A

Receiver position update rate

1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz positioning

Correction data input

CMR™, CMR+™, CMRx™, RTCM 2.x, RTCM 3 (require Rover upgrade)

Correction data output

CMR, CMR+, CMRx, RTCM 2.x, RTCM 3 (require Base upgrade)

Data outputs

NMEA, GSOFF. 1PPS Time Tags (Marine version)

Receiver Upgrades

Location RTK (10/2), (10/10), or (30/30)

Precision RTK Base, Rover or Base/Rover

L5, GLONASS, GALILEO, Compass GNSS¹⁰

28 MB Internal Data Logging option. Moving Base and Heading

2 Watt upgrade for 450 MHz radio

Notes

1 Receiver will operate normally to those temperature limits. Internal batteries will operate from -20 °C to +48 °C

2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices.

3 Depends on SBAS system performance.

4 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.

5 If your receiver has the 2.0 W upgrade, you will experience reduced battery performance compared to the 0.5 W solution.

6 Bluetooth type approvals are country specific. For more information, contact your local Trimble office or representative.

7 When receiver is combined with an SPS555H or other suitable SPS receivers. SPS855 must have Moving base option installed

8 Galileo Commercial Authorization

Developed under a Licence of the European Union and the European Space Agency.

9 Networked RTK PPM values are referenced to the closest physical base station

10 This Trimble SPS Receiver is capable of supporting existing and planned GNSS satellite signals, including GPS, GLONASS, GALILEO, Compass and QZZ, and existing and planned augmentations to these GNSS systems.

Specifications

Trimble SPS855 GNSS Modular Receiver

Specifications subject to change without notice.

© 2012, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and TSC2 are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CMR, CMR+, CMRx, EVEREST, Maxwell, VRS, Zephyr, and Zephyr Geodetic are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners.

Trimble Heavy Civil Construction Business Area

5475 Kellenburger Road

Dayton, Ohio 45424

USA

800-538-7800 (Toll Free)

+1-937-245-5154 Phone

+1-937-233-9441 Fax

www.trimble.com

Trimble Authorized Distribution Partner